

## Specification Sheet

Part Number: 151-02727



Can be easily assembled to convoluted tubing and reliably remain in position Internal rib prevents movement or rattling Multiple configurations to mount to a variety of surfaces Releaseable to allow for maintenance

Conduit Clamps, Size 16, Mounting Hole 6.54, Arrowhead, PA66HIRHS, Black, 900/Pkg

**Article Number** 151-02727

**Type** CDC16AHW6.54

**Color** Black (BK)

**Quantity Per** carton

**Product Description** The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

**Short Description** Conduit Clamps, Size 16, Mounting Hole 6.54, Arrowhead, PA66HIRHS, Black, 900/Pkg

**Global Part Name** CDC16AHW6.54-PA66HIRHS-BK

**Length L (Imperial)** 2.11

**Length L (Metric)** 53.7

**Fixation Method** Arrowhead

**Width W (Imperial)** 0.4

**Width W (Metric)** 10.2

**Bundle Diameter Max (Imperial)** 0.63

**Bundle Diameter Max (Metric)** 16.0

**Height H (Imperial)** 2.76

**Height H (Metric)** 70.1

**Diameter D (Imperial)** 0.69

**Diameter D (Metric)** 17.4

**Mounting Hole Diameter D (Imperial)** 0.26

**Mounting Hole Diameter D (Metric)** 6.54 mm

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	900
<b>Package Quantity (Metric)</b>	900

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)