

## Specification Sheet

Part Number: 151-02727



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 16, Mounting Hole 6.54, Arrowhead, PA66HIRHS, Black, 900/Pkg

Article Number 151-02727

Type CDC16AHW6.54

Color Black (BK)

Quantity Per carton

**Product Description** The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

**Short Description** Conduit Clamps, Size 16, Mounting Hole 6.54, Arrowhead, PA66HIRHS, Black, 900/Pkg

Global Part Name	CDC16AHW6.54-PA66HIRHS-BK
Length L (Imperial)	2.11
Length L (Metric)	53.7
Fixation Method	Arrowhead
Width W (Imperial)	0.4
Width W (Metric)	10.2
Bundle Diameter Max (Imperial)	0.63
Bundle Diameter Max (Metric)	16.0
Height H (Imperial)	2.76
Height H (Metric)	70.1
Diameter D (Imperial)	0.69
Diameter D (Metric)	17.4
Mounting Hole Diameter D (Imperial)	0.26
Mounting Hole Diameter D (Metric)	6.54 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Halogen Free	No
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	900
Package Quantity (Metric)	900

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)