

Specification Sheet

Part Number: 151-02728



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 9 and Size 25, Mounting Hole 6.35 mm, PA66HIRHS, Gray, 450/Pkg

Article Number 151-02728

Type CDC9-25FT6.35

Color Gray (GY)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description Conduit Clamps, Size 9 and Size 25, Mounting Hole 6.35 mm, PA66HIRHS, Gray, 450/Pkg

Global Part Name CDC9-25FT6.35-PA66HIRHS-GY

Length L (Imperial) 3.88

Length L (Metric) 98.5

Fixation Method Fir Tree

Width W (Imperial) 0.4

Width W (Metric) 10.2

Bundle Diameter Max (Imperial) 0.98

Bundle Diameter Max (Metric) 25.0

Height H (Imperial) 3.4

Height H (Metric) 86.35

Diameter D (Imperial) 0.41

Diameter D (Metric) 10.6

Mounting Hole Diameter D (Imperial) 0.25

Mounting Hole Diameter D (Metric) 6.35 mm

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Halogen Free	No
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	450
Package Quantity (Metric)	450

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)