

Specification Sheet

Part Number: 151-02886

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

The connector clip is designed to meet USCAR EWCAP-005-11 clip slot specifications.



Meets installation and extraction requirements of SAE/USCAR-2.

Stud Mount Connector Clip, M5/M6, PA66HIRHSUV, Black, 4000/ctn

Article Number 151-02886

Type SB5-6CC11

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Stud Mount Connector Clip, M5/M6, PA66HIRHSUV, Black, 4000/ctn

Global Part Name SB5-6CC11-PA66HIRHSUV-BK

Length L (Imperial) 1.69

Length L (Metric) 42.93

Variant 5 mm/6 mm Threaded Stud

Width W (Imperial) 0.56

Width W (Metric) 14.21

Height H (Imperial) 0.59

Height H (Metric) 15.0

Mounting Hole Diameter D (Imperial) 0.2 - 0.24

Mounting Hole Diameter D (Metric) 5.0 - 6.0 mm

Mounting Hole Diameter D Min (Imperial) 0.2

Mounting Hole Diameter D Max (Imperial) 0.24

Mounting Hole Diameter D Max (Metric) 6.0

Stud Diameter (Metric) 6.0 mm 5.0 mm

Stud Diameter (Imperial) 0.20 " 0.24

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988