

Specification Sheet

Part Number: 151-02886



Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

The connector clip is designed to meet USCAR EWCAP-005-11 clip slot specifications.

Meets installation and extraction requirements of SAE/USCAR-2.

Stud Mount Connector Clip, M5/M6, PA66HIRHSUV, Black, 4000/ctn

Article Number 151-02886

Type SB5-6CC11

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Stud Mount Connector Clip, M5/M6, PA66HIRHSUV, Black, 4000/ctn

Global Part Name SB5-6CC11-PA66HIRHSUV-BK

Length L (Imperial)	1.69
Length L (Metric)	42.93
Variant	5 mm/6 mm Threaded Stud
Width W (Imperial)	0.56
Width W (Metric)	14.21
Height H (Imperial)	0.59
Height H (Metric)	15.0
Mounting Hole Diameter D (Imperial)	0.197 - 0.236
Mounting Hole Diameter D (Metric)	5.0 - 6.0 mm
Mounting Hole Diameter D Min (Imperial)	0.197
Mounting Hole Diameter D Max (Imperial)	0.2
Mounting Hole Diameter D Max (Metric)	6.0
Stud Diameter (Metric)	6.0 mm 5.0 mm
Stud Diameter (Imperial)	0.20 " 0.24

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)