

## Specification Sheet

Part Number: 151-02896



HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges. HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Conn. Clip w/Oval Fir Tree, 0.60 - 6.00 mm Panel Thickness, Oval Hole 9 X 17, PPS, Silver, 5000/ctn

**Article Number** 151-02896

**Type** CC11B

**Color** Silver (SR)

**Quantity Per** carton

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Oval Fir Tree, 0.60 - 6.00 mm Panel Thickness, Oval Hole 9 X 17, PPS, Silver, 5000/ctn

<b>Global Part Name</b>	CC11B-PPS-SR
<b>Length L (Imperial)</b>	1.18
<b>Length L (Metric)</b>	30.0
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.72
<b>Width W (Metric)</b>	18.20
<b>Height H (Imperial)</b>	0.81
<b>Height H (Metric)</b>	20.60
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	6.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.7
<b>Mounting Hole Diameter D (Metric)</b>	9.0 x 17.0 mm
<b>Material</b>	Polyphenylene Sulfide (PPS)
<b>Material Shortcut</b>	PPS

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988