

Specification Sheet

Part Number: 151-02928



LOC Locking Clamp, 15-19 mm, with 4 x Oval Fir Tree, PA46, Gray, 1000/ctn

Article Number 151-02928

Type LOC15-19FTOVAL

Color Gray (GY)

Features & Benefits

- The 360 degree locking enclosure dynamically fits a range of bundle sizes.
- Clamp can be opened for bundle maintenance.
- Low-profile release tab won't interfere with bundle or nearby routing.
- Non-rotating fir tree demonstrates easy insertion with high extraction resistance.

Quantity Per box

Product Description	The LOC with Oval Fir Tree features HellermannTyton's unique retention clamp attached to a 4x oval fir tree that will not rotate in the mounting hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel. This one design exceeds automotive requirements for the four most common oval sizes: 6.2x12.2 mm, 6.5x12.5 mm, 6.5x13 mm and 7x12 mm.
Short Description	LOC Locking Clamp, 15-19 mm, with 4 x Oval Fir Tree, PA46, Gray, 1000/ctn
Global Part Name	LOC15-19FTOVAL-PA46-GY
Length L (Imperial)	1.67
Length L (Metric)	42.4
Fixation Method	Fir Tree
Width W (Imperial)	0.69
Width W (Metric)	17.63
Bundle Diameter Min (Imperial)	0.59
Bundle Diameter Min (Metric)	15.0
Bundle Diameter Max (Imperial)	0.75
Bundle Diameter Max (Metric)	19.0
Height H (Imperial)	2.5

Height H (Metric)	63.39
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.8
Mounting Hole Diameter D (Imperial)	0.24 x 0.48" 0.26 x 0.49" 0.26 x 0.51" 0.28 x 0.47
Mounting Hole Diameter D (Metric)	6.2 - 13.0 mm
Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Operating Temperature (Metric)	-40°F to +266°F (-40°C to +130°C)
ROHS Complaint	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)