

Specification Sheet

Part Number: 151-02928



The 360 degree locking enclosure dynamically fits a range of bundle sizes

Clamp can be opened for bundle maintenance

Low-profile release tab won't interfere with bundle or nearby routing

Non-rotating fir tree demonstrates easy insertion with high extraction resistance

LOC Locking Clamp, 15-19 mm, with 4 x Oval Fir Tree, PA46, Gray, 1000/ctn

Article Number	151-02928
Type	LOC15-19FTOVAL
Color	Gray (GY)
Quantity Per	box

Product Description	<p>The Locking Clamp is ideal for fastening wire and cable bundles to panels. Its uniquely engineered fir tree holds tightly in pre-stamped hole sizes from 9x12 mm to 9x14 mm. The locking clamp mechanism dynamically fits various bundle sizes, while an integrated cable tie saddle allows installers to add additional cable runs. The clamp is manufactured of an impact-modified Polyamide 6.6 material for increased flexibility, heat resistance and UV stabilization to deliver years of dependable performance. It is easy to install and operate with a single hand and does not require tools, saving time and labor costs.</p>
----------------------------	--

Short Description	LOC Locking Clamp, 15-19 mm, with 4 x Oval Fir Tree, PA46, Gray, 1000/ctn
Global Part Name	LOC15-19FTOVAL-PA46-GY
Length L (Imperial)	1.67
Length L (Metric)	42.4
Fixation Method	Fir Tree
Width W (Imperial)	0.69
Width W (Metric)	17.63
Bundle Diameter Min (Imperial)	0.59
Bundle Diameter Min (Metric)	15.0
Bundle Diameter Max (Imperial)	0.75
Bundle Diameter Max (Metric)	19.0
Height H (Imperial)	2.5
Height H (Metric)	63.39
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27

Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.8
Mounting Hole Diameter D (Imperial)	0.24 x 0.48" 0.26 x 0.49" 0.26 x 0.51" 0.28 x 0.47
Mounting Hole Diameter D (Metric)	6.2 - 13.0 mm

Material Polyamide 4.6 (PA46)

Material Shortcut PA46

Operating Temperature -40°F to +266°F (-40°C to +130°C)

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000