

Specification Sheet

Part Number: 151-02936

Connector clip provides a simple and easy method for mounting connectors to a mounting surface in a variety of applications.

Detailed design includes anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.



Designed to meet push on/pull off forces of SAE/USCAR-2, delivering easy insertion with reliable performance.

Connector Clip with Oval Fir Tree, 17mm, Hole Dia, 12x17mm, PA66HIRHSUV, Black, 3000/carton

Article Number 151-02936

Type CC17FT12X17

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip with Oval Fir Tree, 17mm, Hole Dia, 12x17mm, PA66HIRHSUV, Black, 3000/carton

Global Part Name

CC17FT12X17-PA66HIRHSUV-BK

Length L (Imperial)	1.303
Length L (Metric)	33.1
Fixation Method	Fir Tree for oval holes
Width W (Imperial)	0.799
Width W (Metric)	20.3
Height H (Imperial)	0.834
Height H (Metric)	21.1
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.47 x 0.67
Mounting Hole Diameter D (Metric)	12.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.47
Mounting Hole Diameter D Max (Imperial)	0.47

Mounting Hole Diameter D Max (Metric)	12.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).