

## Specification Sheet

Part Number: 151-02958



Easy assembly without the need of a tool.  
Disc covers mounting hole and minimizes ingress of dust, dirt and water.  
Standard geometry fits common 6.5 mm hole size.

Push Pin, Mounting Hole Dia. 6.5mm, PA66HIRHS, Grey, 5000/carton

<b>Article Number</b>	151-02958
<b>Type</b>	FT6.5 Plug
<b>Color</b>	Gray (GY)
<b>Quantity Per</b>	bag
<b>Product Description</b>	Developed especially for the automotive industry in applications including trunks, doors, wheel housings and dash panels.
<b>Short Description</b>	Push Pin, Mounting Hole Dia. 6.5mm, PA66HIRHS, Grey, 5000/carton
<b>Global Part Name</b>	FT6.5 Plug-PA66HIRHS-GY

<b>Length L (Imperial)</b>	0.76
<b>Length L (Metric)</b>	18.60
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.61
<b>Width W (Metric)</b>	15.70
<b>Height H (Imperial)</b>	0.61
<b>Height H (Metric)</b>	15.40
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.22
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	5.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.27
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 6.9 mm
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS

<b>Flammability</b>	UL 94 HB
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Customs Number</b>	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)