

Specification Sheet

Part Number: 151-02979



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple bracket configurations mount to a variety of surfaces

Releasable to allow for maintenance

Conduit Clamps, Size 10, Mounting Hole 6.5 mm, Offset 40.5 mm, PA66, Black, 50/pkg

Article Number 151-02979

Type CDC10S40.5M6

Color Black (BK)

Quantity Per carton

Product Description

The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description

Conduit Clamps, Size 10, Mounting Hole 6.5 mm, Offset 40.5 mm, PA66, Black, 50/pkg

Global Part Name CDC10S40.5M6-PA66-BK

Length L (Imperial) 2.58

Length L (Metric) 65.5

Variant Clamps

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 0.39

Bundle Diameter Max (Metric) 10.0

Height H (Imperial) 2.0

Height H (Metric) 50.7

Inner Diameter D (Imperial) 0.7

Inner Diameter D (Metric) 17.8

Diameter D (Imperial) 0.43

Diameter D (Metric) 11.0

Nominal Diameter (Imperial) 0.38

Nominal Diameter (Metric) 10.0

Mounting Hole Diameter D (Imperial)	0.26
Mounting Hole Diameter D (Metric)	6.5 mm
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)