

Specification Sheet

Part Number: 151-02983



Can be easily assembled to convoluted tubing and reliably remain in position Internal rib prevents movement or rattling Multiple bracket configurations mount to a variety of surfaces Releasable to allow for maintenance

Conduit Clamps, Size 30, Mounting Hole 6.5 mm, Offset 40.5 mm, PA66HIRHS, Black, 25/pkg

Article Number

151-02983

Type

CDC30S40.5M6

Color

Black (BK)

Quantity Per

carton

Product Description

The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description

Conduit Clamps, Size 30, Mounting Hole 6.5 mm, Offset 40.5 mm, PA66HIRHS, Black, 25/pkg

Global Part Name CDC30S40.5M6-PA66HIRHS-BK

Length L (Imperial) 3.15

Length L (Metric) 79.9

Variant Clamps

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 1.18

Bundle Diameter Max (Metric) 30.0

Height H (Imperial) 3.4

Height H (Metric) 86.3

Inner Diameter D (Imperial) 1.61

Inner Diameter D (Metric) 40.8

Diameter D (Imperial) 1.29

Diameter D (Metric) 32.8

Nominal Diameter (Imperial) 1.25

Nominal Diameter (Metric) 30.0

| | |
|--|--|
| Mounting Hole Diameter D (Imperial) | 0.26 |
| Mounting Hole Diameter D (Metric) | 6.5 mm |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS |
| Flammability | UL 94 HB |
| Halogen Free | No |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 25 |
| Package Quantity (Metric) | 25 |