

Specification Sheet

Part Number: 151-02986



Can be easily assembled to convoluted tubing and reliably remain in position Internal rib prevents movement or rattling Multiple bracket configurations mount to a variety of surfaces Releasable to allow for maintenance

Conduit Clamps, Size 25, Mounting Hole 10.6 mm, Offset 50.0 mm, PA66HIRHS, Black, 50/pkg

Article Number 151-02986

Type CDC25B90OS50M10

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description Conduit Clamps, Size 25, Mounting Hole 10.6 mm, Offset 50.0 mm, PA66HIRHS, Black, 50/pkg

Global Part Name CDC25B90OS50M10-PA66HIRHS-BK

Length L (Imperial) 2.94

Length L (Metric) 74.8

Variant Clamps

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 0.98

Bundle Diameter Max (Metric) 25.0

Height H (Imperial) 4.03

Height H (Metric) 102.4

Inner Diameter D (Imperial) 1.39

Inner Diameter D (Metric) 35.4

Diameter D (Imperial) 1.06

Diameter D (Metric) 27.0

Nominal Diameter (Imperial) 1

Nominal Diameter (Metric) 25.4

Mounting Hole Diameter D (Imperial)	0.42
Mounting Hole Diameter D (Metric)	10.6 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Halogen Free	No
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50