

Specification Sheet

Part Number: 151-02996

Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load.

Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.

Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications.

Low-profile design saves 5 mm of height when installed.

Sealed arrowhead meets USCAR44 push in, pull off and sealing standards.



Conn. Clip w/Oval Arrowhead, 1.2-1.8mm Panel Thick., 6.5x12.5mm Oval, PA66HIRHS/TPE, Black, 4000/ctn

Article Number	151-02996
Type	SAHOVAL1.4TCC7
Color	Black (BK) Gray (GY)
Quantity Per	box

Product Description

HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.

Short Description	Conn. Clip w/Oval Arrowhead, 1.2-1.8mm Panel Thick., 6.5x12.5mm Oval, PA66HIRHS/TPE, Black, 4000/ctn
Global Part Name	SAHOVAL1.4TCC7-PA66HIRHS/TPE-BK/GY
Length L (Imperial)	1.07
Length L (Metric)	27.28
Fixation Method	Arrowhead for oval holes
Variant	6.2 x 12.2 mm 6.5 x 12.5 mm 6.5 x 13.0 mm
Width W (Imperial)	0.89
Width W (Metric)	22.78
Bundle Diameter Max (Imperial)	1.97
Height H (Imperial)	0.69
Height H (Metric)	17.55
Panel Thickness Min (Imperial)	0.05
Panel Thickness Max (Imperial)	0.07
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	1.8

Mounting Hole Diameter D (Imperial) 0.25 x 0.49 " 0.25 x 0.51 " 0.27 x 0.47

Mounting Hole Diameter D (Metric) 6.5 x 13.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Thermoplastic Elastomer (TPE)

Material Shortcut PA66HIRHS TPE

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) No

Package Quantity (Imperial) 4000

Package Quantity (Metric) 4000