

Specification Sheet

Part Number: 151-02996



Arrowhead Mount w/ Seal, 1.2 - 1.8mm Panel Thickness, 6.5x12.5mm Oval, PA66HIRHS/TPE, Black, 4000/ctn

Article Number

151-02996

Type

SAHOVAL1.4TCC7

Color

Black (BK) Gray (GY)

Features & Benefits

- Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load.
- Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.
- Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications.
- Low-profile design saves 5 mm of height when installed.
- Sealed arrowhead meets USCAR44 push in, pull off and sealing standards.

Quantity Per

box

Product Description	HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.
Short Description	Arrowhead Mount w/ Seal, 1.2 - 1.8mm Panel Thickness, 6.5x12.5mm Oval, PA66HIRHS/TPE, Black, 4000/ctn
Global Part Name	SAHOVAL1.4TCC7-PA66HIRHS/TPE-BK/GY
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	222.0
Length L (Imperial)	1.07
Length L (Metric)	27.28
Fixation Method	Arrowhead for oval holes
Width W (Imperial)	0.89
Width W (Metric)	22.78
Bundle Diameter Max (Imperial)	1.97
Height H (Imperial)	0.69
Height H (Metric)	17.55
Panel Thickness Min (Metric)	1.2

Panel Thickness Max (Metric)	1.8
Mounting Hole Diameter D (Imperial)	0.25 x 0.49 " 0.25 x 0.51 " 0.27 x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Thermoplastic Elastomer (TPE)
Material Shortcut	TPE PA66HIRHS
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Package Quantity(Imperial)	4000
Package Quantity (Metric)	4000