

## Specification Sheet

Part Number: 151-02996



Arrowhead Mount w/ Seal, 1.2 - 1.8mm Panel Thickness, 6.5x12.5mm Oval, PA66HIRHSUV/TPE, Black, 4000/ctn

**Article Number** 151-02996

**Type** SAHOVAL1.4TCC7

**Color** Black (BK)

**Features & Benefits**

- Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load.
- Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.
- Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications.
- Low-profile design saves 5 mm of height when installed.
- Sealed arrowhead meets USCAR44 push in, pull off and sealing standards.

**Quantity Per** box

<b>Product Description</b>	HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.
<b>Short Description</b>	Arrowhead Mount w/ Seal, 1.2 - 1.8mm Panel Thickness, 6.5x12.5mm Oval, PA66HIRHSUV/TPE, Black, 4000/ctn
<b>Global Part Name</b>	SAHOVAL1.4TCC7-PA66HIRHSUV/TPE-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	222.0
<b>Length L (Imperial)</b>	1.07
<b>Length L (Metric)</b>	27.28
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.89
<b>Width W (Metric)</b>	22.78
<b>Bundle Diameter Max (Imperial)</b>	1.97
<b>Bundle Diameter Max (Metric)</b>	50.0
<b>Height H (Imperial)</b>	0.69
<b>Height H (Metric)</b>	17.55

**Mounting Hole Diameter D (Imperial)** 0.25 " x 0.49 " 0.25 " x 0.51 " 0.27 " x 0.47

**Mounting Hole Diameter D (Metric)** 6.5 x 12.5 mm 6.5 x 13.0 mm 7.0 x 12.0 mm

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Thermoplastic Elastomer (TPE)

**Material Shortcut** TPE PA66HIRHSUV

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**Use Conditions** For Indoor and Outdoor Use

**Package Quantity(Imperial)** 4000

**Package Quantity (Metric)** 4000