

## Specification Sheet

Part Number: 151-03076



Mini Channel, 1.38" Long, 90° Angle, Fir Tree FT6B, PA66HIRHSUV, Black, 50/box

**Article Number** 151-03076

**Type** BC90FT6B

**Color** Black (BK)

**Features & Benefits**

- The 90-degree configuration of this mini channel creates a solution for routing a wire harness around a corner.
- Design allows the mini channel to be used with a wide range of panel thicknesses and hole diameters.

**Quantity Per** bag

**Product Description** HellermannTyton's Bundling Clips create a solution that allows the harness to be routed around a corner and fixated into the panel at this location.

<b>Short Description</b>	Mini Channel, 1.38" Long, 90° Angle, Fir Tree FT6B, PA66HIRHSUV, Black, 50/box
<b>Global Part Name</b>	BC90FT6B-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	0.98
<b>Length L (Metric)</b>	25.0
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.06
<b>Width W (Metric)</b>	1.5
<b>Height H (Imperial)</b>	0.96
<b>Height H (Metric)</b>	24.5
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.22
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	5.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 " - 0.27
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 6.9 mm

**Mounting Hole Diameter D Max (Metric)** 6.9

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL 94 HB

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 50

**Package Quantity (Metric)** 50