

Specification Sheet

Part Number: 151-03096



Mount and tie combination makes it easy to service bundles in the field. Eliminates the need for multiple sized diameter clamps.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.

Medium Torque Cable Tie Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA666V0, Black, 500/pkg

Article Number 151-03096

Type HDM321

Color Black (BK)

Quantity Per carton

Product Description The arched H-profile of the saddle allows for broad surface contact with the bundle, minimizing pinching and crushing of wires, and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T150 or Wide Strap Cable Ties. Low fire hazard material is designed specifically for rail applications.

Short Description Medium Torque Cable Tie Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA666V0, Black, 500/pkg

Global Part Name	HDM321-PA666V0-BK
Length L (Imperial)	1.82
Length L (Metric)	46.5
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.98
Width W (Metric)	25.0
Height H (Imperial)	0.81
Height H (Metric)	20.7
Cable Tie Width Max (Imperial)	0.5
Cable Tie Width Max (Metric)	12.7
Mounting Hole Diameter D (Imperial)	0.3125
Mounting Hole Diameter D (Metric)	8.31 mm
Material	Polyamide 6.6 + Polyamide 6 V0 (PA66/6V0)
Material Shortcut	PA666V0

Flammability	Low smoke generation Halogen-free Low generation of toxic gases and corrosive acid Limited fire hazard UL 94 V-0
Halogen Free	Yes
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Maximum Torque (kgf-cm)	553.02
Maximum Torque (lbf-ft)	40
ROHS Compliant	Yes
Certification/Specification	ASTM 1354 ASTM E 662 Exova NFPA130: 2017 ASTM E 162
Package Quantity (Imperial)	500
Package Quantity (Metric)	500

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)