

## Specification Sheet

Part Number: 151-03097



Mount and tie combination makes it easy to service bundles in the field. Eliminates the need for multiple sized diameter clamps.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.

Medium Torque Cable Tie Mount, Mounting Hole Dia. 0.375", Max Torque 40.0 lb - ft, PA666V0, Black, 500/pkg

**Article Number** 151-03097

**Type** HDM401

**Color** Black (BK)

**Quantity Per** carton

**Product Description** The arched H-profile of the saddle allows for broad surface contact with the bundle, minimizing pinching and crushing of wires, and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T150 or Wide Strap Cable Ties. Low fire hazard material is designed specifically for rail applications.

**Short Description** Medium Torque Cable Tie Mount, Mounting Hole Dia. 0.375", Max Torque 40.0 lb - ft, PA666V0, Black, 500/pkg

|  |   |
|--|---|
| <b>Global Part Name</b>                    | HDM401-PA666V0-BK                         |
| <b>Length L (Imperial)</b>                 | 1.82                                      |
| <b>Length L (Metric)</b>                   | 46.5                                      |
| <b>Fixation Method</b>                     | Screw Mounting and Rivet                  |
| <b>Width W (Imperial)</b>                  | 0.98                                      |
| <b>Width W (Metric)</b>                    | 25.0                                      |
| <b>Height H (Imperial)</b>                 | 0.81                                      |
| <b>Height H (Metric)</b>                   | 20.7                                      |
| <b>Cable Tie Width Max (Imperial)</b>      | 0.5                                       |
| <b>Cable Tie Width Max (Metric)</b>        | 12.7                                      |
| <b>Mounting Hole Diameter D (Imperial)</b> | 0.405                                     |
| <b>Mounting Hole Diameter D (Metric)</b>   | 10.29 mm                                  |
| <b>Material</b>                            | Polyamide 6.6 + Polyamide 6 V0 (PA66/6V0) |
| <b>Material Shortcut</b>                   | PA666V0                                   |

|                                    |  |
|------------------------------------|--|
| <b>Flammability</b>                | UL 94 V-0 Low generation of toxic gases and corrosive acid Limited fire hazard Low smoke generation Halogen-free |
| <b>Halogen Free</b>                | Yes  |
| <b>Operating Temperature</b>       | -40°F to +248°F (-40°C to +120°C)  |
| <b>Maximum Torque (kgf-cm)</b>     | 553.02   |
| <b>Maximum Torque (lbf-ft)</b>     | 40   |
| <b>ROHS Compliant</b>              | Yes  |
| <b>Certification/Specification</b> | ASTM 1354 ASTM E 662 ASTM E 162 Exova   NFPA130: 2017  |
| <b>Package Quantity (Imperial)</b> | 500  |
| <b>Package Quantity (Metric)</b>   | 500  |