

Specification Sheet

Part Number: 151-03099

Compact size fits most mounting applications.
Simple to install with screws or rivets.

Two-hole attachment with four-way entry for cable tie.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.



Screw Mount Cable Tie Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA666V0, Black, 100/pkg

Article Number	151-03099
Type	MB4
Color	Black (BK)
Quantity Per	carton
Product Description	HellermannTyton screw fastened mounting bases are used with 18 through 50 lb cable ties to provide stability when securing bundles. Cable ties can be inserted parallel or perpendicular to the wire bundles. Low fire hazard material is designed specifically for rail applications.
Short Description	Screw Mount Cable Tie Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA666V0, Black, 100/pkg

Global Part Name	MB4-PA666V0-BK
Length L (Imperial)	1.12
Length L (Metric)	28.5
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	1.12
Width W (Metric)	28.5
Cable Ties	T18 - T50
Height H (Imperial)	0.19
Height H (Metric)	4.8
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	5.4
Mounting Hole Diameter D (Imperial)	0.18
Mounting Hole Diameter D (Metric)	4.6 mm
Mounting Hole Diameter D Max (Metric)	4.0
Mounting Hole Centers (Imperial)	0.8

Material	Polyamide 6.6/6, V0 (PA666V0)
Material Shortcut	PA666V0
Flammability	Low generation of toxic gases and corrosive acid Limited fire hazard Halogen-free UL 94 V-0 Low smoke generation
Halogen Free	Yes
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS Compliant	Yes
Certification/Specification	ASTM E 662 Exova NFPA130: 2017 ASTM E 162 ASTM 1354
Package Quantity (Imperial)	100
Package Quantity (Metric)	100

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)