

Specification Sheet

Part Number: 151-03101

Separates bundles to help prevent chafing and wear. Single bundles can be mounted on top of the mount, or two bundles can be separated using the two side saddles; giving the mount versatility.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.



Low Profile Screw Mount, 1.8" x 0.98", 0.25" Hole, PA666V0, Black, 500/pkg

Article Number 151-03101

Type LPM25

Color Black (BK)

Quantity Per carton

Product Description Low-profile mounts secure bundles close to mounting surfaces, making them ideal for applications where bundle mounting space is limited. These are secured to the mounting surface with a 0.25" mechanical fastener and feature a counter bore for easy access with a socket. The mount accommodates cable ties up to 0.5" in width. Low fire hazard material is designed specifically for rail applications.

Short Description Low Profile Screw Mount, 1.8" x 0.98", 0.25" Hole, PA666V0, Black, 500/pkg

Global Part Name	LPM25-PA666V0-BK
Length L (Imperial)	1.8
Length L (Metric)	45.1
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.98
Width W (Metric)	24.9
Cable Ties	T50 - T250
Height H (Imperial)	0.66
Height H (Metric)	16.7
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.7 mm
Mounting Hole Diameter D Max (Metric)	6.7
Material	Polyamide 6.6/6, V0 (PA666V0)
Material Shortcut	PA666V0

Flammability	Limited fire hazard Halogen-free Low smoke generation UL 94 V-0 Low generation of toxic gases and corrosive acid
Halogen Free	Yes
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS Compliant	Yes
Certification/Specification	Exova NFPA130: 2017 ASTM E 162 ASTM 1354 ASTM E 662
Package Quantity (Imperial)	500
Package Quantity (Metric)	500

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)