

Specification Sheet

Part Number: 151-03103



Mount and tie combination makes it easy to service bundles in the field. Eliminates the need for multiple sized diameter clamps.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.

High Torque Mount, Mounting Hole Dia. 0.327", Max Torque 114.0 lb - ft, PA666V0, Black, 500/pkg

Article Number 151-03103

Type HDM320

Color Black (BK)

Quantity Per carton

Product Description The saddle design minimizes pinching and crushing of wires and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T150 or Wide Strap Cable Ties. Metal bushing provides strength for high-torque applications. Low fire hazard material is designed specifically for rail applications.

Short Description High Torque Mount, Mounting Hole Dia. 0.327", Max Torque 114.0 lb - ft, PA666V0, Black, 500/pkg

| | |
|--|---|
| Global Part Name | HDM320-PA666V0-BK |
| Length L (Imperial) | 1.82 |
| Length L (Metric) | 46.5 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 0.98 |
| Width W (Metric) | 25.0 |
| Height H (Imperial) | 0.81 |
| Height H (Metric) | 20.7 |
| Cable Tie Width Max (Imperial) | 0.5 |
| Cable Tie Width Max (Metric) | 12.7 |
| Mounting Hole Diameter D (Imperial) | 0.327 |
| Mounting Hole Diameter D (Metric) | 8.31 mm |
| Material | Polyamide 6.6 + Polyamide 6 V0 (PA66/6V0) |
| Material Shortcut | PA666V0 |

| | |
|------------------------------------|--|
| Flammability | Limited fire hazard Halogen-free UL 94 V-0 Low generation of toxic gases and corrosive acid Low smoke generation |
| Halogen Free | Yes |
| Operating Temperature | -40°F to +248°F (-40°C to +120°C) |
| Maximum Torque (kgf-cm) | 1576.11 |
| Maximum Torque (lbf-ft) | 114 |
| ROHS Compliant | Yes |
| Certification/Specification | ASTM 1354 Exova NFPA130: 2017 ASTM E 662 ASTM E 162 |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |