

Specification Sheet

Part Number: 151-03155



Integrated design allows for easy insertion by hand

0.75–1.25 mm panel thickness range allows for multiple applications

Double-compression design that accommodates various sizes of wire and cable

Presents a high extraction force for withstanding extreme conditions

Low Profile Metal Edge Clip, 0.75 - 1.25mm Panel Thickness, 4.1 - 7mm Cable Range, SS304, 5000/ctn

Article Number 151-03155

Type MSC2LP1

Color Metal (ML)

Quantity Per carton

Product Description

Designed for more confined areas, HellermannTyton's Low Profile Metal Edge Clip provides an excellent alternative to managing wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, the Metal Edge Clip has a high extraction force that tolerates extreme environments and provides assurance that the cables are secure on a panel. The Metal Edge Clip is simple to install and can easily be removed with a flathead screwdriver.

Short Description	Low Profile Metal Edge Clip, 0.75 - 1.25mm Panel Thickness, 4.1 - 7mm Cable Range, SS304, 5000/ctn
Global Part Name	MSC2LP1-SS304-ML
Length L (Imperial)	0.71
Length L (Metric)	18.1
Width W (Imperial)	0.41
Width W (Metric)	10.3
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	4.1
Bundle Diameter Max (Imperial)	0.28
Bundle Diameter Max (Metric)	7.0
Depth D (Imperial)	0.649
Depth D (Metric)	16.48
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.05
Panel Thickness Min (Metric)	0.75
Panel Thickness Max (Metric)	1.25

Material	Stainless Steel (SS304)
Material Shortcut	SS304
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Listed (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	7326908695

