

## Specification Sheet

Part Number: 151-03251



Easy assembly without the need of a tool.  
Disc covers mounting hole and reduces vibration.

Fir tree mount provides easy insertion and excellent extraction resistance.

Push Pin w/Round Fir Tree, 0.6-12.5mm Panel Thickness, 6.1-6.7mm Dia, PPS, Bk, 5000/ctn

<b>Article Number</b>	151-03251
<b>Type</b>	FT6.5SDLGBPLUG
<b>Color</b>	Silver (SR)
<b>Quantity Per</b>	carton
<b>Product Description</b>	Push pins allow the fastening of multiple parts together with a simple press of the thumb.
<b>Short Description</b>	Push Pin w/Round Fir Tree, 0.6-12.5mm Panel Thickness, 6.1-6.7mm Dia, PPS, Bk, 5000/ctn
<b>Global Part Name</b>	FT6.5SDLGBPLUG-PPS-SR

<b>Length L (Imperial)</b>	0.84
<b>Length L (Metric)</b>	21.27
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.30
<b>Width W (Metric)</b>	7.80
<b>Height H (Imperial)</b>	0.84
<b>Height H (Metric)</b>	21.27
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.49
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	12.50
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 6.7 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	6.7
<b>Disc Diameter (Metric)</b>	17

<b>Disc Diameter (Imperial)</b>	0.69
<b>Material</b>	Polyphenylene Sulfide (PPS)
<b>Material Shortcut</b>	PPS
<b>Flammability</b>	UL 94 V-0
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Compliant (Article 33)</b>	No
<b>Package Quantity (Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000