

Specification Sheet

Part Number: 151-03318

Connector clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.



A wide assortment of styles is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Conn. Clip w/Oval Fir Tree, 0.6-6.75mm Panel Thick, 6.0-13.2mm Hole, PA66HIRHSUV, Black, 4500/ctn

Article Number 151-03318

Type CCAMPFTOVAL

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Conn. Clip w/Oval Fir Tree, 0.6-6.75mm Panel Thick, 6.0-13.2mm Hole, PA66HIRHSUV, Black, 4500/ctn

Global Part Name CCAMPFTOVAL-PA66HIRHSUV-BK

Length L (Imperial) 0.93

Length L (Metric) 23.63

Width W (Imperial) 0.69

Width W (Metric) 17.63

Height H (Imperial) 0.93

Height H (Metric) 23.68

Mounting Hole Diameter D (Imperial) 0.24 - 0.52

Mounting Hole Diameter D (Metric) 6.0 - 13.2 mm

Mounting Hole Diameter D Min (Imperial) 0.24

Mounting Hole Diameter D Max (Imperial) 0.52

Mounting Hole Diameter D Max (Metric) 13.2

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	4500
Package Quantity (Metric)	4500

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)