

Specification Sheet

Part Number: 151-03513

Connector clip design complies to USCAR EWCAP-005-7 clip slot design and testing specifications.

Mount design provides low insertion with high extraction resistance for easy installation and reliable performance.



features a long fir tree for extensive panel ranges with 6.5mm holes.

Connector Clip w/ Fir Tree, 7mm, 0.60-6.0 mm Panel Thickness, PA66HIRHSUV, Black, 2000/ctn

Article Number 151-03513

Type CC7OSFT6

Color Black (BK)

Quantity Per carton

Product Description 7 mm connector clips made with new ergonomically friendly fir tree and connector clip design that complies with USCAR design and performance standards.

Short Description Connector Clip w/ Fir Tree, 7mm, 0.60-6.0 mm Panel Thickness, PA66HIRHSUV, Black, 2000/ctn

Global Part Name CC7OSFT6-PA66HIRHSUV-BK

Length L (Imperial)	1.26
Length L (Metric)	32.1
Fixation Method	Fir Tree
Width W (Imperial)	0.94
Width W (Metric)	24.0
Height H (Imperial)	0.63
Height H (Metric)	16.1
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.26 (hexagonal);0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

