

Specification Sheet

Part Number: 151-03540

Smaller footprint for applications where space is constrained.
Easily attaches to existing bolts, studs and threaded rods, eliminating the need for additional hardware.

One-piece ratchet closure design allows for easy installation during pre- or final assembly.

Clamp interior is designed to guide and center bundles to reduce pinching.

Tension Tabs and EVO®-series hand tools available for consistently accurate clamp pressure.



Bolt Mount Ratchet Clamp for Low Torque, 0.50 - 0.77" Bundle, 0.26" Hole, PA66HIRHSUV, BK, 160/bag

Article Number	151-03540
Type	CMRCBLM6
Color	Black (BK)
Quantity Per	bag

Product Description	<p>The Center Mount Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Specially designed for locations with space constraints or where offset mounting options are not ideal. Available with a compression limiter for crush resistance in high-torque applications, or in all plastic for low- to medium-torque applications. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal or addition of cables simply by inserting a flat-head screwdriver. In this way, the clamp can be reused without removing it from the mounting surface.</p>
Short Description	<p>Bolt Mount Ratchet Clamp for Low Torque, 0.50 - 0.77" Bundle, 0.26" Hole, PA66HIRHSUV, BK, 160/bag</p>
Global Part Name	<p>CMRCBLM6-PA66HIRHSUV-BK</p>
Minimum Tensile Strength (Imperial)	<p>200</p>
Minimum Tensile Strength (Metric)	<p>889</p>
Length L (Imperial)	<p>3.39</p>
Length L (Metric)	<p>86.1</p>
Fixation Method	<p>Screw Mount</p>
Width W (Imperial)	<p>1.38</p>
Width W (Metric)	<p>35.1</p>
Bundle Diameter Min (Imperial)	<p>0.50</p>
Bundle Diameter Min (Metric)	<p>12.7</p>

Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.56
Height H (Imperial)	1.20
Height H (Metric)	30.4
Diameter D (Imperial)	0.25
Diameter D (Metric)	6.3
Bolt Size	0.26 "
Mounting Hole Diameter D (Imperial)	0.26
Mounting Hole Diameter D (Metric)	M6
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes

Package Quantity (Imperial) 150

Package Quantity (Metric) 150