

## Specification Sheet

Part Number: 151-03545

Smaller footprint for applications where space is constrained.  
Easily attaches to existing bolts, studs and threaded rods, eliminating the need for additional hardware.

Cover/stopper inside the clamp prevents stud from touching the cable bundle, minimizing chaffing and protecting bundle from damage.

One-piece ratchet closure design allows for easy installation during pre- or final assembly.

Clamp interior is designed to guide and center bundles to reduce pinching.

Tension Tabs and EVO®-series hand tools available for consistently accurate clamp pressure.



Stud Mount Ratchet Clamp for M8 Stud, 0.50 - 0.77" Bundle Dia, PA66HIRHSUV, Black, 160/bag

Article Number	151-03545
Type	CMRCBSMM8
Color	Black (BK)
Quantity Per	bag

Product Description	The Center Mount Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Specially designed for locations with space constraints or where offset mounting options are not ideal. Easily attaches to existing studs or bolts without the need for additional hardware. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal or addition of cables simply by inserting a flat-head screwdriver. In this way, the clamp can be reused without removing it from the mounting surface.
Short Description	Stud Mount Ratchet Clamp for M8 Stud, 0.50 - 0.77" Bundle Dia, PA66HIRHSUV, Black, 160/bag
Global Part Name	CMRCBSMM8-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	200
Minimum Tensile Strength (Metric)	889
Length L (Imperial)	3.39
Length L (Metric)	86.1
Fixation Method	Stud Mount
Width W (Imperial)	1.38
Width W (Metric)	35.1
Bundle Diameter Min (Imperial)	0.50
Bundle Diameter Min (Metric)	12.7

Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.56
Height H (Imperial)	1.20
Height H (Metric)	30.4
Bolt Size	0.33 "
Stud Diameter (Metric)	M8
Stud Diameter (Imperial)	0.33
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	150

