

Specification Sheet

Part Number: 151-03651

No drilling or extra hardware required – just position on steel surface.

Magnetic mounts are reliable even in debris, dirt and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse and reposition capabilities allow for a flexible mounting solution.

Saddle included to prevent kinking of cables.

Easily remove without leaving residue behind.



Magnetic Bridle Ring with Saddle, Large, 2" Dia Ring, Neodymium Magnet/PP/ST, 90lb Pull Force, 10/box

| | |
|----------------|------------------------|
| Article Number | 151-03651 |
| Type | MAGBR90L-S |
| Color | Yellow (YE) Metal (ML) |
| Quantity Per | box |

| | |
|-----------------------|--|
| Product Description | Magnetic bridle rings route cables by securing to steel surfaces without the need for a mounting hole. Simply attach cables within the bridle ring saddle and position the magnet onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. Magnetic bridle rings are ideal for supporting communication and data cables. The additional saddle helps prevent kinking of wires. The mounts are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts. |
| Short Description | Magnetic Bridle Ring with Saddle, Large, 2" Dia Ring, Neodymium Magnet/PP/ST, 90lb Pull Force, 10/box |
| Global Part Name | MAGBR90L-S-NDFEB45M/PP/ST-ML/YE |
| Fixation Method | Magnet |
| Height H (Imperial) | 3.90 |
| Height H (Metric) | 99.1 |
| Diameter D (Imperial) | 1.57 |
| Diameter D (Metric) | 40.0 |
| Material | Polypropylene (PP) Steel (ST) Neodymium alloy 45M (NDFEB45M) |
| Material Shortcut | PP ST NDFEB45M |
| Halogen Free | Yes |

| | |
|------------------------------|----------------------------------|
| UV Resistant (Yes/No) | No |
| Plenum Rating | AH-1 |
| Operating Temperature | -40°F to +176°F (-40°C to +80°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| UL Listed (US and Canada) | Yes |
| UL Listed (US) | Yes |
| Package Quantity (Imperial) | 10 |
| Package Quantity (Metric) | 10 |
| Customs Number | 8505110070 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)