

## Specification Sheet

Part Number: 151-03823



Patented retention design on clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement. Controlled flex and angled entry promote easy installation.

Independent rotation allows for adjustable routing orientation.

Cable tie accommodates wide range of secondary bundle sizes.

MOC Clip, 19 mm, with 6.5mm Fir Tree, PA66HIRHSUV, Black, 100/bag

Article Number 151-03823

Type MOC19FT6.5

Color Black (BK)

Quantity Per bag

Product Description The MOC with Round Fir Tree features HellermannTyton's unique retention clip with an integrated fir tree to fit securely in a 6.5 (+/-0.4) mm hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel.

Short Description MOC Clip, 19 mm, with 6.5mm Fir Tree, PA66HIRHSUV, Black, 100/bag

Global Part Name MOC19FT6.5-PA66HIRHSUV-BK

Length L (Imperial) 1.07

Length L (Metric) 27.3

Fixation Method Fir Tree

Bundle Diameter Min (Imperial) 0.67

Bundle Diameter Min (Metric) 17.0

Bundle Diameter Max (Imperial) 0.86

Bundle Diameter Max (Metric) 21.8

Height H (Imperial) 1.91

Height H (Metric) 48.5

Depth D (Imperial) 0.47

Depth D (Metric) 12.0

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.22

Panel Thickness Min (Metric) 0.60

Panel Thickness Max (Metric) 5.5

Mounting Hole Diameter D (Imperial)	0.25 " HEX; 0.26
Mounting Hole Diameter D (Metric)	6.5 mm (+/- 0.4 mm) 6.35 mm (hexagonal)
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100