

Specification Sheet

Part Number: 151-04064

Reversed orientation ensures PV cables are completely enclosed inside panel, reducing exposure to wind, snow and ice that can dislodge cables from mounting clips.

Clip can be preloaded onto cable so it can be blind-mounted under panel.

Larger thumb pad is more comfortable for installers, resulting in less strain and faster installations.

1 - 3 mm panel thickness range fits a wide range of panels.

Double-compression design accommodates various wire and cable sizes.



Heavy Duty Reverse Barb Metal Edge Clip, 1–3mm Panel Thickness, 5–7.6mm Cable Range, SS304, 100/bag

Article Number 151-04064

Type MSC2RB

Color Metal (ML)

Quantity Per bag

Product Description	HellermannTyton's Reverse Barb Metal Edge Clip provides an excellent alternative to managing wire and PV cables where plastic fasteners are not the preferred method. Designed for effortless insertion, this Solar Clip has a high extraction force that tolerates extreme environments and provides assurance that the cables remain securely fastened to a panel. The clip is similar in design to the MSC2 clip, except orientation is at 180 degrees, which positions the PV cables inside the panel frame.
Short Description	Heavy Duty Reverse Barb Metal Edge Clip, 1–3mm Panel Thickness, 5–7.6mm Cable Range, SS304, 100/bag
Global Part Name	MSC2RB-SS304-ML
Length L (Imperial)	0.95
Length L (Metric)	24.1
Width W (Imperial)	0.75
Width W (Metric)	19.1
Height H (Imperial)	0.57
Height H (Metric)	14.4
Material	Stainless Steel (SS304)
Material Shortcut	SS304
Halogen Free	Yes

UV Resistant (Yes/No)	Yes
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	7326908695

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)