

Specification Sheet

Part Number: 151-04074

Soft TPE over-mold prevents axial slide/rotation and protects sensitive HV cables.

Modular connector clip design eliminates the need for investment in expensive tools for TPE products or upsetting of tubes and pipes.

Fine-pitch ratchet provides controlled grip for a range of pipe sizes with one part.

Fully enclosed clamp prevents slip, crush and fallout under vacuum.

Release feature opens by inserting a screwdriver, allowing the clamp to be reused or serviced without removing it from mounting surface..



Soft-Grip Ratchet O-Clamp, 17mm Connector Clip, .61-.79" Bundle Dia., PA66HIRHSUV/TPE, Blk, 1000/ctn

Article Number	151-04074
Type	SGROC15.5-20CLIP17
Color	Black (BK)
Quantity Per	carton

Product Description	Designed for fluid routing and high-voltage cable management, the soft-grip Ratchet O-Clamp comes with a TPE liner to protect routings and keep them in position. HellermannTyton's connector clips provide a single method to mount connectors to various surfaces in a variety of applications. Clips can be paired with brackets for custom routing needs. Developed for tight spaces, this clamp maintains a low profile while providing an adjustable grip for a range of bundle sizes.
Short Description	Soft-Grip Ratchet O-Clamp, 17mm Connector Clip, .61-.79" Bundle Dia., PA66HIRHSUV/TPE, Blk, 1000/ctn
Global Part Name	SGROC15.5-20CLIP17-PA66HIRHSUV/TPE-BK
Minimum Tensile Strength (Imperial)	100
Minimum Tensile Strength (Metric)	445
Length L (Imperial)	1.46
Length L (Metric)	37.0
Fixation Method	Connector Clip
Width W (Imperial)	0.81
Width W (Metric)	20.5
Bundle Diameter Min (Imperial)	0.61
Bundle Diameter Min (Metric)	15.5
Bundle Diameter Max (Imperial)	0.79
Bundle Diameter Max (Metric)	20.0

Height H (Imperial)	1.46
Height H (Metric)	37.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Thermoplastic Elastomer (TPE)
Material Shortcut	TPE PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)