

Specification Sheet

Part Number: 151-04075

Soft TPE over-mold prevents axial slide/rotation and protects sensitive HV cables.

Long 6.5 mm fir tree allows clip to be installed in panels up to 6 mm thick and hole sizes from 6.1-7.0 mm.

Fine-pitch ratchet provides controlled grip for a range of pipe sizes with one part.

Fully enclosed clamp prevents slip, crush and fallout under vacuum.

Release feature opens by inserting a screwdriver, allowing the clamp to be reused or serviced without removing it from mounting surface. .



Soft-Grip Ratchet O-Clamp, Fir Tree Mnt, 0.61 - 0.79" Bundle, 6.5mm Hole, PA66HIRHSUV/TPE, Blk, 1000/ctn

Article Number 151-04075

Type SGROC15.5-20FT6.5

Color Black (BK)

Quantity Per carton

Product Description Designed for fluid routing and high-voltage cable management, the soft-grip Ratchet O-Clamp comes with a TPE liner to protect routings and keep them in position. An integrated fir tree provides a secure grip into round mounting holes with no additional hardware. Developed for tight spaces, this clamp maintains a low profile while providing an adjustable grip for a range of bundle sizes.

Short Description	Soft-Grip Ratchet O-Clamp, Fir Tree Mnt, 0.61 - 0.79" Bundle, 6.5mm Hole, PA66HIRHSUV/TPE, Blk, 1000/ctn
Global Part Name	SGROC15.5-20FT6.5-PA66HIRHSUV/TPE-BK
Minimum Tensile Strength (Imperial)	100
Minimum Tensile Strength (Metric)	445
Length L (Imperial)	1.46
Length L (Metric)	37.0
Fixation Method	Fir Tree
Width W (Imperial)	0.81
Width W (Metric)	20.5
Bundle Diameter Min (Imperial)	0.61
Bundle Diameter Min (Metric)	15.5
Bundle Diameter Max (Imperial)	0.79
Bundle Diameter Max (Metric)	20.0
Height H (Imperial)	1.81
Height H (Metric)	46.0
Panel Thickness Min (Imperial)	0.02

Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.26 (hexagonal); 0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)
Material	Thermoplastic Elastomer (TPE) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	TPE PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000

Package Quantity (Metric) 1000

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)