

Specification Sheet

Part Number: 151-04351

Long 6.5 mm fir tree allows clip to be installed in panels up to 6 mm thick and for hole sizes from 6.1-7.0 mm.

Fine-pitch ratchet provides controlled grip for a range of pipe sizes with one part.

Fully enclosed clamp prevents slip, crush and fallout under vacuum.

Release feature opens by inserting a screwdriver, allowing the clamp to be reused or serviced without removing it from mounting surface.



Ratchet O-Clamp, Fir Tree Mount, 0.73 - 0.89" Bundle Dia., 6.5mm Hole Dia., PA66HIRHSUV, Blk, 1000/ctn

Article Number	151-04351
Type	ROC18.5-22.5FT6.5
Color	Black (BK)
Quantity Per	carton
Product Description	The Ratchet O-Clamp is designed for tight spaces, maintaining a low profile while providing an adjustable closure for a range of bundle sizes. An integrated fir tree provides a secure grip into round mounting holes with no additional hardware.
Short Description	Ratchet O-Clamp, Fir Tree Mount, 0.73 - 0.89" Bundle Dia., 6.5mm Hole Dia., PA66HIRHSUV, Blk, 1000/ctn

Global Part Name ROC18.5-22.5FT6.5-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 100

Minimum Tensile Strength (Metric) 445

Length L (Imperial) 1.46

Length L (Metric) 37.0

Fixation Method Fir Tree

Width W (Imperial) 0.81

Width W (Metric) 20.5

Bundle Diameter Min (Imperial) 0.73

Bundle Diameter Min (Metric) 18.5

Bundle Diameter Max (Imperial) 0.89

Bundle Diameter Max (Metric) 22.5

Height H (Imperial) 1.81

Height H (Metric) 46.0

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.24

Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.26 (hexagonal); 0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.1 - 6.6 mm (hexagonal) 6.1 - 7.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000

Customs Number

3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)