

## Specification Sheet

Part Number: 151-04352



Versatile, high-performance fir tree design demonstrates easy installation with high pull-out resistance in the four most common hole sizes.

Fine-pitch ratchet provides controlled grip for a range of pipe sizes with one part.

Fully enclosed clamp prevents slip, crush and fallout under vacuum.

Release feature opens by inserting a screwdriver, allowing the clamp to be reused or serviced without removing it from mounting surface.

Ratchet O-Clamp, Oval Fir Tree Mount, .73-.89" Bundle Dia., PA66HIRHSUV, Black, 1000/ctn

Article Number 151-04352

Type ROC18.5-22.5FTOVAL

Color Black (BK)

Quantity Per carton

Product Description The Ratchet O-Clamp is designed for tight spaces, maintaining a low profile while providing an adjustable closure for a range of bundle sizes. An integrated fir tree provides a secure grip into oval mounting holes with no additional hardware.

Short Description Ratchet O-Clamp, Oval Fir Tree Mount, .73-.89" Bundle Dia., PA66HIRHSUV, Black, 1000/ctn

Global Part Name ROC18.5-22.5FTOVAL-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 100

Minimum Tensile Strength (Metric) 445

Length L (Imperial) 1.46

Length L (Metric) 37.0

Fixation Method Fir Tree

Width W (Imperial) 0.81

Width W (Metric) 20.5

Bundle Diameter Min (Imperial) 0.73

Bundle Diameter Min (Metric) 18.5

Bundle Diameter Max (Imperial) 0.89

Bundle Diameter Max (Metric) 22.5

Height H (Imperial) 1.81

Height H (Metric) 46.0

Panel Thickness Min (Imperial) 0.02

Panel Thickness Max (Imperial) 0.27

Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 "; 0.26 x 0.49 "; 0.26 x 0.51 "; 0.28 x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 12.5 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)