

Specification Sheet

Part Number: DSWS50HSK2



Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter 0.625 - 6", Black, PA66HS, 50/pkg

Article Number	151-06502
Type	DSWS5
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•H-profile of the saddles allows for broad surface contact with the bundle, which minimizes pinching and crushing of the bundle.•Swivels in 360-degree motion to accommodate any area.•Accommodates T50–T250 ties to handle both light-duty and heavy-duty applications.
Quantity Per	bag

Product Description

These saddle spacers are installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate and prevent chafing and wear. The mounts can be easily rotated by hand, allowing the bundles to be crossed and rotated at any angle. Cable ties, which secure the bundles, are used with the mounts. The dual swivel saddle spacers accommodate cable ties up to 1/2" wide.

Short Description

Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter 0.625 - 6", Black, PA66HS, 50/pkg

Global Part Name

DSWS5-PA66HS-BK

Length L (Imperial)

1.60

Length L (Metric)

40.6

Width W (Imperial)

1.0

Width W (Metric)

25.4

Bundle Diameter Min (Imperial)

0.7

Bundle Diameter Min (Metric)

16.0

Bundle Diameter Max (Imperial)

6.0

Bundle Diameter Max (Metric)

152.0

Cable Ties

T50 - T250

Height H (Imperial)

0.9

Height H (Metric)

23.6

Cable Tie Width Max (Imperial)

0.5

Cable Tie Width Max (Metric)

12.7

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Minimum Extraction Force (Imperial)	250.0
Minimum Extraction Force (Metric)	1112
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909987
Content Unit(BMEcat)	pcs.
Weight (Metric)	1.5