

## Specification Sheet

Part Number: HDM321HIHSUVH4



Mount and tie combination makes it easy to service bundles in the field. Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.

Eliminates the needs for multiple sized fix diameter clamps.

Medium Torque Cable Tie Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

**Article Number** 151-07100

**Type** HDM321

**Color** Black (BK)

**Quantity Per** bag

**Product Description** The arched H-profile of the saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles, and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

**Short Description** Medium Torque Cable Tie Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

**Global Part Name**

HDM321-PA66HIRHSUV-BK

**Length L (Imperial)**

1.81

**Length L (Metric)**

46.0

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.95

**Width W (Metric)**

24.0

**Height H (Imperial)**

0.81

**Height H (Metric)**

20.7

**Cable Tie Width Max (Imperial)**

0.50

**Cable Tie Width Max (Metric)**

12.7

**Mounting Hole Diameter D (Imperial)**

0.3125

**Mounting Hole Diameter D (Metric)**

8.31 mm

**Mounting Hole Diameter D Min (Imperial)**

0.3125

**Mounting Hole Diameter D Max (Imperial)**

0.3125

**Mounting Hole Diameter D Max (Metric)**

7.9

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Maximum Torque (kgf-cm)</b>	553
<b>Maximum Torque (lbf-ft)</b>	40
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988