

## Specification Sheet

Part Number: 151-10953



Opening on the tag allows the Q Tie to be easily inserted, providing a secure identification solution.

Q Tag, 5.3" x 2.6", For Q18 thru Q50 ties, PA66, White, 25/bag

**Article Number** 151-10953

**Type** QT10065R

**Color** White (WH)

**Quantity Per** bag

**Product Description**

Q-tags are used to identify a cable or a cable bundle and is secured with a Q-tie. The Q-tag's flag design allows the user to quickly read or scan the printed information. The tags can be marked by hand with a marker pen (T82 series) or with a printed adhesive label. HellermannTyton offers a complete printing solution for Q-tags: printers, labels, ribbons, and market leading label design software, TagPrint Pro. Using Q-ties and Q-tags gives users the confidence that cables and cable bundles are safely secured and the text is highly visible.

<b>Short Description</b>	Q Tag, 5.3" x 2.6", For Q18 thru Q50 ties, PA66, White, 25/bag
<b>Global Part Name</b>	QT10065R-PA66-WH
<b>Length L (Metric)</b>	135.0
<b>Fixation Method</b>	Others
<b>Variant</b>	Other
<b>Width W (Imperial)</b>	5.31
<b>Width W (Metric)</b>	135.0
<b>Thickness T (Imperial)</b>	0.055
<b>Thickness T (Metric)</b>	1.4
<b>Height H (Imperial)</b>	2.64
<b>Height H (Metric)</b>	67.05
<b>Cable Tie Width Max (Imperial)</b>	0.2
<b>Cable Tie Width Max (Metric)</b>	4.7
<b>Material</b>	Polyamide 6.6 (PA66)

<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909988