

## Specification Sheet

Part Number: MSMP5/109C2



Cable Tie Mounting Plate, 8.05" x .62", .2" Hole Dia, .3" Max Tie Width, PA66, Natural, 100/pkg

<b>Article Number</b>	151-25519
<b>Type</b>	MSMP5/10
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Mounting plates allow multiple bundles to run parallel.</li><li>• The mounts are secured using two screws, while the bundles are attached using cable ties in any of the available slots.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Mounting Plates allow multiple cables to be run in parallel. Mounts are secured with two screws. Cables are attached to the plates by running a cable tie through any of the available slots.
<b>Short Description</b>	Cable Tie Mounting Plate, 8.05" x .62", .2" Hole Dia, .3" Max Tie Width, PA66, Natural, 100/pkg

**Global Part Name**

MSMP5/10-PA66-NA

**Length L (Imperial)**

8.05

**Length L (Metric)**

204.47

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.62

**Width W (Metric)**

15.8

**Height H (Imperial)**

.21

**Height H (Metric)**

5.30

**Cable Tie Width Max (Imperial)**

0.3

**Cable Tie Width Max (Metric)**

7.6

**Mounting Hole Diameter D (Imperial)**

0.2

**Mounting Hole Diameter D (Metric)**

5.1 mm

**Mounting Hole Diameter D Max (Metric)**

5.1

**Mounting Hole Centers (Imperial)**

1.5

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL | ANSI/UL 1565 UL | ANSI/UL 62275 UL | ANSI/UL 746B

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 1.9