

Specification Sheet

Part Number: LKCRF19C2



The low-profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole

This mount is ideal for use in applications where space is limited

Low Profile Rivet Mount, 0.938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg

Article Number	151-27000
Type	LKCRF1
Color	Natural (NA)
Quantity Per	bag
Product Description	Low Profile Rivet Mount, 0.938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg
Short Description	Low Profile Rivet Mount, 0.938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg
Global Part Name	LKCRF1-PA66-NA

Length L (Imperial)	0.938
Length L (Metric)	24.0
Fixation Method	with Rivet (Mounts)
Width W (Imperial)	0.47
Width W (Metric)	12.0
Cable Ties	T18 - T50
Height H (Imperial)	0.157
Height H (Metric)	3.99
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	4.8
Panel Thickness Max (Imperial)	0.134
Panel Thickness Max (Metric)	3.40
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.4 mm
Mounting Hole Diameter D Max (Imperial)	0.255
Mounting Hole Diameter D Max (Metric)	6.4

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).