

## Specification Sheet

Part Number: LKCRF19C2



Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg

**Article Number** 151-27000

**Type** LKCRF1

**Color** Natural (NA)

**Features & Benefits**

- The low-profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole.
- This mount is ideal for use in applications where space is limited.

**Quantity Per** bag

**Product Description**

HellermannTyton's Mounts with Rivets are ideal for use in applications where space is limited and is designed to secure wiring bundles. Fastens with the drive rivet through a predrilled hole.

<b>Short Description</b>	Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg
<b>Global Part Name</b>	LKCRF1-PA66-NA
<b>Length L (Imperial)</b>	0.938
<b>Length L (Metric)</b>	24.0
<b>Fixation Method</b>	with Rivet (Mounts)
<b>Width W (Imperial)</b>	0.47
<b>Width W (Metric)</b>	12.0
<b>Cable Ties</b>	T18 - T50
<b>Height H (Imperial)</b>	0.157
<b>Height H (Metric)</b>	3.99
<b>Panel Thickness Max(Imperial)</b>	0.134
<b>Panel Thickness Max (Metric)</b>	3.40
<b>Mounting Hole Diameter D (Imperial)</b>	0.25
<b>Mounting Hole Diameter D (Metric)</b>	6.4 mm
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.255

**Mounting Hole Diameter D Max (Metric)** 6.4

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**ROHS Complaint** Yes

**Use Conditions** For Indoor Use Only

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988