

Specification Sheet

Part Number: LKCRF19C2



Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg

| | |
|--------------------------------|--|
| Article Number | 151-27000 |
| Type | LKCRF1 |
| Color | Natural (NA) |
| Features & Benefits | <ul style="list-style-type: none">• The low-profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole.• This mount is ideal for use in applications where space is limited. |
| Quantity Per | bag |
| Product Description | HellermannTyton's Mounts with Rivets are ideal for use in applications where space is limited and is designed to secure wiring bundles. Fastens with the drive rivet through a predrilled hole. |
| Short Description | Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg |

Global Part Name

LKCRF1-PA66-NA

Length L (Imperial)

0.938

Length L (Metric)

24.0

Fixation Method

with Rivet (Mounts)

Width W (Imperial)

0.47

Width W (Metric)

12.0

Cable Ties

T18 - T50

Height H (Imperial)

0.157

Height H (Metric)

3.99

Panel Thickness Max(Imperial)

0.134

Panel Thickness Max (Metric)

3.40

Mounting Hole Diameter D (Imperial)

0.25

Mounting Hole Diameter D (Metric)

6.4 mm

Mounting Hole Diameter D Max (Imperial)

0.255

Mounting Hole Diameter D Max (Metric)

6.4

| | |
|---------------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909987 |