

Specification Sheet

Part Number: LKCRF19C2



Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg

Article Number	151-27000
Type	LKCRF1
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none">• The low-profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole.• This mount is ideal for use in applications where space is limited.
Quantity Per	bag
Product Description	HellermannTyton's Mounts with Rivets are ideal for use in applications where space is limited and is designed to secure wiring bundles. Fastens with the drive rivet through a predrilled hole.
Short Description	Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 100/pkg

Global Part Name

LKCRF1-PA66-NA

Length L (Imperial)

0.938

Length L (Metric)

24.0

Fixation Method

with Rivet (Mounts)

Width W (Imperial)

0.47

Width W (Metric)

12.0

Cable Ties

T18 - T50

Height H (Imperial)

0.157

Height H (Metric)

3.99

Panel Thickness Max(Imperial)

0.134

Panel Thickness Max (Metric)

3.40

Mounting Hole Diameter D (Imperial)

0.25

Mounting Hole Diameter D (Metric)

6.4 mm

Mounting Hole Diameter D Max (Imperial)

0.255

Mounting Hole Diameter D Max (Metric)

6.4

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988