

Specification Sheet

Part Number: MB5A0A2F4



Acrylic Adhesive Cable Tie Mount, 1.49" x 1.49", Use With T18-T150 Cable Tie, PA66, Black, 250/pkg

Article Number 151-28604

Type MB5A

Color Black (BK)

Features & Benefits

- For use with HellermannTyton T18 - T150 cable ties to provide stability when securing bundles.
- 4-way opening allows cable ties to be installed parallel or perpendicular to bundles.
- The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 2.1 lb.
- Two predrilled holes extend mounting options and solutions.
- Extended adhesive liner is easy to remove quickly.

Quantity Per bag

Product Description	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.
Short Description	Acrylic Adhesive Cable Tie Mount, 1.49" x 1.49", Use With T18-T150 Cable Tie, PA66, Black, 250/pkg
Global Part Name	MB5A-PA66-BK
Length L (Imperial)	1.49
Length L (Metric)	37.7
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	1.49
Width W (Metric)	37.7
Cable Ties	T18 - T150
Height H (Imperial)	.28
Height H (Metric)	7.1
Cable Tie Width Max (Imperial)	0.35
Cable Tie Width Max (Metric)	8.9
Mounting Hole Diameter D (Imperial)	0.19

Mounting Hole Diameter D (Metric) 4.8 mm

Mounting Hole Diameter D Max (Metric) 4.8

Mounting Hole Centers (Imperial) 1.0

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Adhesive Acrylate with base of acrylic foam

Flammability UL 94 V2 (excluding adhesive)

Adhesive Operating Temperature -31°F to +158°F (-35 °C to +70 °C)

Operating Temperature (Metric) -40°F to +185°F (-40°C to +85°C)

ROHS Complaint Yes

Package Quantity(Imperial) 250

Package Quantity (Metric) 250

Customs Number 3926909988

