

Specification Sheet

Part Number: MB5A0A2F4



Adhesive Cable Tie Mount, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66/Acrylate, Black, 250/pkg

Article Number	151-28604
Type	MB5A
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• For use with 18 and 30 pound cable ties to provide stability when securing bundles.• Secures with rubber based adhesive backing and/or two or four screws.• 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.
Quantity Per	bag
Product Description	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Short Description

Adhesive Cable Tie Mount, 1.49" x 1.49", .35" Max Tie Width, .19" Hole Dia, PA66/Acrylate, Black, 250/pkg

Global Part Name

MB5A-PA66-BK

Length L (Imperial)

1.49

Length L (Metric)

37.7

Fixation Method

Screw Mounting and Adhesive

Width W (Imperial)

1.49

Width W (Metric)

37.7

Cable Ties

T18 - T150

Height H (Imperial)

.28

Height H (Metric)

7.10

Cable Tie Width Max (Imperial)

0.35

Cable Tie Width Max (Metric)

8.9

Mounting Hole Diameter D (Imperial)

0.19

Mounting Hole Diameter D (Metric)

4.8 mm

Mounting Hole Diameter D Max (Metric)

4.8

Mounting Hole Centers (Imperial)

1.0

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Adhesive	Acrylate with base of acrylic foam
Flammability	UL 94 V2 (excluding adhesive)
Adhesive Operating Temperature	-4°F to +122°F (-20°C to +50°C)
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	250
Customs Number	3926909987