

## Specification Sheet

Part Number: MB4SHA0C2

For use with HellermannTyton T18 - T50 cable ties to provide stability when securing bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 1.1 lb.

A predrilled hole extends mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, Black, 100/pkg

**Article Number** 151-29200

**Type** MB4SHA

**Color** Black (BK)

**Quantity Per** bag

**Product Description** MB4SHA adhesive mounts are for use with HellermannTyton T18 - T50 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have a predrilled hole to extend mounting options.

**Short Description** Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, Black, 100/pkg

**Global Part Name** MB4SHA-PA66-BK

**Length L (Imperial)** 1.12

**Length L (Metric)** 28.3

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 1.12

**Width W (Metric)** 28.3

**Cable Ties** T18 - T50

**Height H (Imperial)** .23

**Height H (Metric)** 5.8

**Cable Tie Width Max (Imperial)** 0.18

**Cable Tie Width Max (Metric)** 4.6

**Mounting Hole Diameter D (Imperial)** 0.15

**Mounting Hole Diameter D (Metric)** 3.9 mm

**Mounting Hole Diameter D Max (Metric)** 3.9

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Adhesive</b>	Synthetic rubber with base of polyethylene foam
<b>Flammability</b>	UL 94 V2 (excluding adhesive)
<b>Adhesive Operating Temperature</b>	0°F to +150°F (-18 °C to +66 °C)
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988