

## Specification Sheet


Part Number: MB4SHA10H4

For use with HellermannTyton T18 - T50 cable ties to provide stability when securing bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 1.1 lb.

A predrilled hole extends mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 500/pkg

<b>Article Number</b>	151-29206
<b>Type</b>	MB4SHA
<b>Color</b>	White (WH)
<b>Quantity Per</b>	bag
<b>Product Description</b>	MB4SHA adhesive mounts are for use with HellermannTyton T18 - T50 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have a predrilled hole to extend mounting options.
<b>Short Description</b>	Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 500/pkg

**Global Part Name** MB4SHA-PA66-WH

**Length L (Imperial)** 1.12

**Length L (Metric)** 28.3

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 1.12

**Width W (Metric)** 28.3

**Cable Ties** T18 - T50

**Height H (Imperial)** .23

**Height H (Metric)** 5.8

**Cable Tie Width Max (Imperial)** 0.18

**Cable Tie Width Max (Metric)** 4.6

**Mounting Hole Diameter D (Imperial)** 0.15

**Mounting Hole Diameter D (Metric)** 3.9 mm

**Mounting Hole Diameter D Max (Metric)** 3.9

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Adhesive</b>	Synthetic rubber with base of polyethylene foam
<b>Flammability</b>	UL 94 V-2 (excluding adhesive)
<b>Adhesive Operating Temperature</b>	0°F to +150°F (-18 °C to +66 °C)
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988