

Specification Sheet

Part Number: MB4SHA10H4

For use with HellermannTyton T18 - T50 cable ties to provide stability when securing bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 1.1 lb.

A predrilled hole extends mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 500/pkg

| | |
|---------------------|---|
| Article Number | 151-29206 |
| Type | MB4SHA |
| Color | White (WH) |
| Quantity Per | bag |
| Product Description | MB4SHA adhesive mounts are for use with HellermannTyton T18 - T50 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have a predrilled hole to extend mounting options. |
| Short Description | Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 500/pkg |

| | |
|---------------------------------------|-----------------------------|
| Global Part Name | MB4SHA-PA66-WH |
| Length L (Imperial) | 1.12 |
| Length L (Metric) | 28.3 |
| Fixation Method | Screw Mounting and Adhesive |
| Width W (Imperial) | 1.12 |
| Width W (Metric) | 28.3 |
| Cable Ties | T18 - T50 |
| Height H (Imperial) | .23 |
| Height H (Metric) | 5.8 |
| Cable Tie Width Max (Imperial) | 0.18 |
| Cable Tie Width Max (Metric) | 4.6 |
| Mounting Hole Diameter D (Imperial) | 0.15 |
| Mounting Hole Diameter D (Metric) | 3.9 mm |
| Mounting Hole Diameter D Max (Metric) | 3.9 |

| | |
|--------------------------------|---|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Adhesive | Synthetic rubber with base of polyethylene foam |
| Flammability | UL 94 V-2 (excluding adhesive) |
| Adhesive Operating Temperature | 0°F to +150°F (-18 °C to +66 °C) |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |