

Specification Sheet

Part Number: MSBT1200HIRHSP2



Saddle Mount For Button Head Tie, 0.44"–0.82" Mounting Hole, PA66HIRHSUV, Black, 10/pkg

| | |
|---------------------|---|
| Article Number | 151-29302 |
| Type | MSBT120 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•Secures up to three bundles for multiple routing.•Provides parallel spacing between frame rail and adjacent bundles to reduce wear.•Manufactured with a pilot bushing which prevent the cable tie from chafing against the burr edge of the mounting hole. |
| Quantity Per | bag |

Product Description

HellermannTyton's saddle mounts are designed to be used with button head ties, the saddle mount stands off bundles from frame rails, providing clearance from bolts and other protrusions for protection against abrasion. This mount also allows the flow-through of salt, dirt, and other impurities from the road which prevent unwanted build-up on hoses and harnesses. The tie is snapped into the mount which allows the strap and tie assembly to be pre-installed on the frame rail or panel. The mount can secure three separate bundles, providing parallel spacing between the frame rail and adjacent bundles. The saddle mount is manufactured with a pilot busing which prevents the cable tie from chafing against the burr edge of the mounting hole.

Short Description

Saddle Mount For Button Head Tie, 0.44"-0.82" Mounting Hole, PA66HIRHSUV, Black, 10/pkg

Global Part Name

MSBT120-PA66HIRHSUV-BK

Length L (Imperial)

1.9

Length L (Metric)

48.3

Width W (Imperial)

0.65

Width W (Metric)

16.5

Bundle Diameter 1st Loop Max (Imperial)

6.0

Bundle Diameter 1st Loop Max (Metric)

152.4

Bundle Diameter 2nd Loop Max (Imperial)

1.0

Bundle Diameter 2nd Loop Max (Metric)

25.4

Height H (Imperial)

0.8

Height H (Metric)

20.6

Panel Thickness Min(Imperial)

0.16

Panel Thickness Max(Imperial) 0.75

Panel Thickness Min (Metric) 4.1

Panel Thickness Max (Metric) 19.05

Mounting Hole Diameter D (Metric) 11.2 - 20.8 mm

Mounting Hole Diameter D Min (Imperial) .440

Mounting Hole Diameter D Max (Imperial) .820

Mounting Hole Diameter D Max (Metric) 20.8

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature (Metric) -65°F to +230°F (-54°C to +110°C)

ROHS Complaint Yes

Package Quantity(Imperial) 10

Package Quantity (Metric) 10

Customs Number 3926909987

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)