

## Specification Sheet

Part Number: S2HM250HIRHSH1



2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHSUV, Black, 500/pkg

**Article Number** 151-29403

**Type** S2HM25

**Color** Black (BK)

### Features & Benefits

- Separates bundles from wear and chafing, providing additional longevity.
- Hexagonal retention feature (S2HM25) captures a bolt or nut requiring tool access from the back side only.
- A socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt (S2CM25.)
- Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.

**Quantity Per** bag

<b>Product Description</b>	HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, the H-profile on the saddle mount provides a tight circumferential loop on large and small bundles. Cable ties up to 1/2" wide are used to secure the bundles.
<b>Short Description</b>	2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHSUV, Black, 500/pkg
<b>Global Part Name</b>	S2HM25-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	1.80
<b>Length L (Metric)</b>	45.0
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	1.2
<b>Width W (Metric)</b>	30.0
<b>Bundle Diameter Max (Imperial)</b>	3.5
<b>Bundle Diameter Max (Metric)</b>	89.0
<b>Cable Ties</b>	T50 - T250
<b>Height H (Imperial)</b>	0.90
<b>Height H (Metric)</b>	23.0
<b>Cable Tie Width Max (Imperial)</b>	0.5

<b>Cable Tie Width Max (Metric)</b>	12.7
<b>Mounting Hole Diameter D (Imperial)</b>	0.24
<b>Mounting Hole Diameter D (Metric)</b>	6.35 mm (hexagonal) 6.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Metric)</b>	6.0
<b>Stud Diameter (Metric)</b>	6.35 mm
<b>Stud Diameter (Imperial)</b>	0.25
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Use Conditions</b>	For Indoor and Outdoor Use

<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	9.88